



TSM621FWX IPS Security Container

Product Data Sheet

TECHNICAL SPECIFICATIONS

Model	TSM621FWX
Rec. Heat Load:	1700 – 6300 Watts
Rack:	32Ux29"D roll-out rack, 500lb capacity
Weight:	2145lbs
Dimensions:	62.5"H x 27"W x 52"D* add 2.75" to width for vents add 4.6" to depth for handle & cable exit *(Custom Depths Available)
Door Opening:	59.75"H x 24.25"W
Internal Space:	61.75"H x 26.25"W x 38.5"D
Power:	115VAC, 50/60Hz, 2.8A (cooling fans)
Noise Levels:	42dBA at 75°F up to 63dBA at 95°F
Cable Count:	Up to 35 (Cat5) incoming "Black" Up to 75 (Cat5) outgoing "Red"*** **(Optional Enlarged Cable Entry Available)

GSA CLASS 5 FEDERAL SPECIFICATIONS:

PHYSICAL PROTECTION: Federal Specification AA-C-2786
 20 man-hours against surreptitious entry
 30 man-minutes against covert entry
 10 man-minutes against forced entry

LOCK SPECIFICATION: Federal Specification FF-L-2740
 Approved Locks: Kaba Mas X-10 and S&G 2740



FEATURES AT A GLANCE

- Largest IPS Container on the market!
- GSA approved alternative to CAA or facility build-out
- Highest level class 5 physical protection available
- 32Ux29"D roll-out rack with removable service tracks
- Low noise temperature controlled cooling system
- Two feed-thru style cable entries for Red/Black separation
- Mounting bracket for optional PDS junction box
- 5-outlet power strip with 15ft cord included
- Flat bottom design reduces floor loading

OPTIONS & ACCESSORIES

Part No.	Description
TSSPG-BC	SIPRGuard HDMI/USB/Ethernet on-off gateway with two-factor authentication for secure SIPRNet access
TSM1924LT-SLSF	Laptop Slide Tray for 19" Rack, 1U x 24"D, 45lb capacity, with cable management arm
TSM192036-FSF	Fixed Shelf for 19" Rack, 1U telescoping design fits 20-36" deep racks, 100 lb capacity
TS-RS1215-RA	1U Rack-Mount Power Strip, 120V, 15A, 12 outlets 5-15R with 15-ft. Cord
TSM1010-JB	PDS Junction Box, 10x8x10, Right Side Door Opening
TSM511-ECB	Enlarged Cable Box for High Cable Counts (up to 144 Cat5)
TSM2752-CSTR	Caster Base for 27"Wx52"D models, (4) 5" Dia. Locking Wheels
TSM4X5-SP	Floor Loading Spreader Plate, 4ft x 5ft
TSMST8PDU-SGD	SafeGuard Remote Monitor, Alarm & Control System: dial rotation, lock status, door position, temp & power, with remote equipment power shutdown



TSM621FWX